

FocusLCDs.com

RELIABILITY AND SUPPORT FOR LESS

TFT | CHARACTER | VATN | FSC | SEGMENT
CUSTOM | REPLACEMENT

LCD's Made Simple


Phone-480-503-4295 | Email-NOPP@FocusLCD.com

16 x 4 VATN Display Module

Overview

4 line VATN, 5x8 dots includes
cursor, Controller (ST7066 or Equivalent),
+5V power supply only, 1/16 duty cycle,
Interface : Option 6800, SPI, I2C

VATN Character 16x4



Feature

1. 5x8 dots includes cursor
2. Built-in controller (ST7066 or Equivalent)
3. 5V power supply only
4. 1/16 duty cycle
5. LED type : Green / Blue / Red / White / Y- G
6. LED can be driven by PIN1, PIN2 or K
7. Interface : Option 6800, SPI, I2C

Pin No.	Symbol	Description
1	V _{SS}	Ground
2	V _{DD}	Power supply for logic
3	V _O	Contrast Adjustment
4	RS	Data/ Instruction select signal
5	R/W	Read/Write select signal
6	E	Enable signal
7	DB0	Data bus line
8	DB1	Data bus line
9	DB2	Data bus line
10	DB3	Data bus line
11	DB4	Data bus line
12	DB5	Data bus line
13	DB6	Data bus line
14	DB7	Data bus line
15	V _{EE}	Negative Voltage Output
16	K	Power supply for B/L -

Mechanical Data

Item	Standard Value	Unit
Module Dimension	87.0 x 60.0	mm
Viewing Area	62.0 x 26.0	mm
Mounting Hole	82.0 x 55.0	mm
Character Size	2.95 x 4.75	mm

Electrical Characteristics

Item	Symbol	Standard Value	Unit
		typ.	
Input Voltage	VDD	5.0	V
Recommended LCD Driving Voltage for Normal Temp. Version module @25°C	VDD-VO	6.50	V

Display Character Address Code

Display position	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
DD RAM Address	00	01														0F
DD RAM Address	40	41														4F
DD RAM Address	10	11														1F
DD RAM Address	50	51														5F