


Pin	Name
1	VLED-
2	VLED+
3	GND
4	VDD
5	RO
6	R1
7	R2
8	R3
9	R4
10	R5
11	R6
12	R7
13	G0
14	G1
15	G2
16	G3
17	G4
18	G5
19	G6
20	G7
21	B0
22	B1
23	B2
24	B3
25	B4
26	B5
27	B6
28	B7
29	GND
30	PCLK
31	DISP
32	HSYNC
33	VSYNC
34	DE
35	NC
36	GND
37	XR(NC)
38	YD(NC)
39	XL(NC)
40	YU(NC)



Display type:TFT/Normally white
 Display mode:Transmissive
 color depth:16.7M Colors
 Interface Type: 24 BIT R.G.B
 Wide viewing: 12 o'clock
 Backlight: White Backlight 12 LED
 TYP: Vf=19.2V If=40mA
 Operating temperature: -10° C ~ +60° C
 Storage temperature: -20° C ~ +70° C
 ROHS COMPLIANT PRODUCT

ReV	Revision content description	Date	TOLERANCE	DRAWING NAME	Unit
A	FIRST	2014/04/17	TOLERANCE UNLESS OTHERWISE SPECIFIED X.X±0.3 X.XX±0.2	Drawn	mm
				Checked	
				Approve	Page 1/1



Scale	1:1	Symbol	Approve