



FOCUS LCDs

LCDs MADE SIMPLE®

Ph. 480-503-4295 | LCD@FocusLCDs.com

TFT | OLED | CHARACTER | GRAPHIC | UWVD | SEGMENT | CUSTOM

Character Display Module

Part Number

C162A-FTW-DS23

Overview:

- 16x2 Character LCD
- FSTN Gray
- 80x36 mm Module
- 4-bit or 8-bit MCU Interface(s)
- White LED Backlight
- Transflective
- Special Temp Range
- 3.3V
- LCD IC: ST7066U-0A
- RoHS Compliant

Character LCD Features

Characters: 16x2

Interface(s): 4-bit or 8-bit MPU


RoHS Compliant

General Information Items	Specification	Unit	Note
	Main Panel		
Viewing Area (VA)	66.0 (H) x 16.0 (V)	mm	--
LCD Type	FSTN Positive	--	--
Viewing Angle	12:00	O'Clock	--
Polarizer	Transflective	--	--
Backlight Type	LED	--	--
Backlight Color	White	--	--
LCD IC	ST7066U-0A	--	--
Character Height	5.55	mm	--
Operating Temperature	-30 to +80	°C	--
Storage Temperature	-35 to +85	°C	--

Mechanical Information

Item		Min.	Typ.	Max.	Unit	Note
Module Size	Horizontal (H)	--	80.0	--	mm	--
	Vertical (V)	--	36.0	--	mm	--
	Depth (D)	--	13.20	--	mm	--
Weight		--	35	--	g	Approximate


1. Outline Dimensions



2. Input Terminal Pin Assignment

NO.	Symbol	Description
1	VSS	Ground, 0V.
2	VDD	Logic Power Supply.
3	V0	Operating voltage for LCD.
4	RS	Data / Instruction Register Select (H: Data Signal, L: Instruction Signal).
5	R/W	Read / Write (H: Read Mode, L: Write Mode).
6	E	Enable Signal.
7~14	DB0~DB7	Data Bus.
15	LED_A	Backlight Anode.
16	LED_K	Backlight Cathode.

3. Block Diagram



4. LCD Optical Characteristics

Item	Symbol	Condition	Min	Typ.	Max	Unit
Contrast Ratio	CR	25°C	--	12	--	ms
Rise Time	T _r		--	160	240	
Fall Time	T _f		--	100	150	
Viewing Angle	Hor.	Θ _L	--	70	--	degree
		Θ _R	--	40	--	
	Ver.	Θ _T	--	55	--	
		Θ _B	--	55	--	

5. Electrical Characteristics

5.1 Absolute Maximum Rating

Characteristics	Symbol	Min	Max	Unit
Supply Voltage for Logic	VDD-VSS	-0.3	5.5	V
Supply Voltage for LCD	VDD-V0	0	10.0	V
Operating Temperature	TOP	-30	+80	°C
Storage Temperature	TST	-35	+85	°C

NOTE: If the absolute maximum rating of the above parameters is exceeded, even momentarily, the quality of the product may be degraded. Absolute maximum ratings specify the values which the product may be physically damaged if exceeded. Be sure to use the product within the range of the absolute maximum ratings.

5.2 DC Electrical Characteristics

Characteristics	Symbol	Condition	Min	Typ.	Max	Unit
Supply Voltage for Logic	VDD-VSS		3.1	3.3	5.5	V
Supply Voltage for LCD	VDD-V0	VDD= 3.3V	--	3.2	--	V
Input Voltage	V-IH	H Level	2.2	--	VDD	V
	V-IL	L Level	0	--	0.6	V
Supply Current for Logic	Icc		--	1	1.2	mA
Supply Current for LCD	Io		0.15	0.22	0.27	mA


Condition:

1. VDD = 3.3V
2. 1/16 Duty, 1/5 Bias

5.3 AC Characteristics


Timing Specification at Ta=25°C, VDD=5V±10%, VSS=0
Write Mode

Characteristics	Symbol	Test Pin	Min	Typ.	Max	Unit
E Cycle Time	tc	E	500	--	--	ns
E Rise Time	tR	E	--	--	25	ns
E Fall Time	tF	E	--	--	25	ns
E-pulse Width (H, L)	tw	E	220	--	--	ns
R/W and RS Set-up Time	tsul	R/W,RS	40	--	--	ns
R/W and RS Hold Time	tH1	R/W,RS	10	--	--	ns
Data Set-up Time	tsu2	DB0-DB7	60	--	--	ns
Data Hold Time	tH2	DB0-DB7	10	--	--	ns



Read Mode

Characteristics	Symbol	Test Pin	Min	Typ.	Max	Unit
E Cycle Time	t_c	E	500	--	--	ns
E Rise Time	t_R	E	--	--	25	ns
E Fall Time	t_F	E	--	--	25	ns
E-pulse Width (H, L)	t_w	E	220	--	--	ns
R/W and RS Set-up Time	t_{su}	R/W,RS	40	--	--	ns
R/W and RS Hold Time	t_H	R/W,RS	10	--	--	ns
Data Output Delay	t_D	DB0-DB7	--	--	120	ns
Data Hold Time	t_{DH}	DB0-DB7	20	--	--	ns



5.4 Backlight Characteristics

Unless specified, the ambient temperature Ta=25C


Characteristics	Symbol	Condition	Min	Typ.	Max	Unit
Supply Voltage	Vf		3.0	3.1	3.3	V
Forward Current	Imf	Vf=3.1V	--	15	--	mA
Reverse Voltage	Vr		--	--	2.0	V
Power Dissipation	Pd	Vf=3.1V	--	--	--	mW
Peak Wavelength	λ_p	Vf=3.1V	--	--	--	nm
Luminance	Lv	Vf=3.1V	90	220	--	Cd/mm
LED Lifetime	L	Vf=3.1V	--	50,000	--	hours

6. Instruction Table


Function	R	RD	DD	DD	DD	DD	DD	DD	Description	Execu Time* (Max)						
	SW	B	B	B	B	B	B									
	7	6	5	4	3	2	1	0								
Clear Display	0	0	0	0	0	0	0	0	1	Clears entire display and returns the cursor to home position (address 0)	1.64mS					
Return Home	0	0	0	0	0	0	0	0	1	X	Return the cursor to the home position. DD RAM contents remain unchanged. Set DD RAM address to zero.	1.64mS				
Entry mode set	0	0	0	0	0	0	0	1	1	S	/	D	Set cursor moving direction and enable the shift of the display. These operations are performed during data write/read of DD RAM/CG RAM. 1/D=1: increment; 1/D=0: decrement; S=1: whole display shift when data is written.	40μS		
Display ON/OFF control	0	0	0	0	0	0	1	D	C	B			Set display (D), cursor (C) and blinking of cursor (B) ON/OFF. D=1: display ON; D=0: display OFF. C=1: Cursor ON; C=0: cursor OFF. B=1: Blink ON; B=0, Blink OFF.	40μS		
Cursor or Display shift	0	0	0	0	0	1	S	R	X	X	/	/	C	L	Move the cursor and shift the display without changing DDRAM contents. S/C=1: Display Shift; S/C=0: Cursor move. R/L=1: shift to right; R/L=0: shift to left.	40μS
Function Set	0	0	0	0	1	D	N	F	X	X				Set interface data length (DL), number of display lines (N) and character font (F). DL=1: 8 bits; DL=0: 4 bits. N=1: 2 lines; N=0: 1 lines. F=1: 5X11 dots; F=0: 5X7 dots.	40μS	
Set CG RAM add	0	0	0	1						ACG				Set CG RAM address. CG RAM data is sent and received after this setting.	40μS	
Set DD RAM Add	0	0	1							ADD				Set DD RAM address. DD RAM data is sent and received after this setting.	40μS	
Read BF & Addr	0	1	B							AC				Read BUSY FLAG (BF) and the contents of the address counter. BF=1: internal operation; BF=0: can accept instruction.	0μS	
Write Data to RAM	1	0								WRITE DATA				Write data into DD RAM or CG RAM.	40μS**	
Read Data from RAM	1	0								READ DATA				Read data from DD RAM or CG RAM.	40μS**	

7. Initializing By Instruction

8-bit Interface Mode(Condition: fosc=270kHz)



4-bit Interface Mode(Condition: fosc=270kHz)



8. Standard Character Pattern

Lower 4 Bits \ Upper 4 Bits	0000	0001	0010	0011	0100	0101	0110	0111	1000	1001	1010	1011	1100	1101	1110	1111
xxxx0000	CG RAM (1)			0	1	P	`	P				-	9	3	α	ρ
xxxx0001	(2)		!	1	A	Q	a	q			。	ア	チ	△	ä	q
xxxx0010	(3)		"	2	B	R	b	r			「	イ	ツ	×	ß	θ
xxxx0011	(4)		#	3	C	S	c	s			」	ウ	テ	モ	ε	∞
xxxx0100	(5)		\$	4	D	T	d	t			、	エ	ト	ト	μ	Ω
xxxx0101	(6)		%	5	E	U	e	u			・	オ	ナ	1	σ	ü
xxxx0110	(7)		&	6	F	V	f	v			ヲ	カ	ニ	ヨ	ρ	Σ
xxxx0111	(8)		'	7	G	W	g	w			ア	キ	ヌ	ラ	g	π
xxxx1000	(1)		<	8	H	X	h	x			イ	ク	ネ	リ	r	∞
xxxx1001	(2))	9	I	Y	i	y			ウ	ケ	ル	ル	'	y
xxxx1010	(3)		*	:	J	Z	j	z			エ	コ	ハ	レ	j	ƒ
xxxx1011	(4)		+	;	K	[k	{			オ	サ	ヒ	ロ	*	π
xxxx1100	(5)		,	<	L	¥	l	l			カ	シ	フ	ワ	φ	π
xxxx1101	(6)		-	=	M]	m	}			ユ	ヌ	ハ	ン	も	÷
xxxx1110	(7)		.	>	N	^	n	‡			ヨ	セ	ホ	°	ñ	
xxxx1111	(8)		/	?	O	_	o	€			ッ	ソ	マ	°	ö	■

9. Cautions and Handling

General Precautions:

1. LCD panel is made of glass. Avoid excessive mechanical shock or applying strong pressure onto the surface of display area.
2. The polarizer used on the display surface is easily scratched and damaged. Extreme care should be taken when handling. To clean dust or dirt off the display surface, wipe gently with cotton, or other soft material soaked with isopropyl alcohol, ethyl alcohol or trichlorotrifluoroethane. Do not use water, ketone or aromatics and never scrub hard.
3. Do not tamper in any way with the tabs on the metal frame.
4. Do not make any modification on the PCB without consulting.
5. When mounting the LCM, make sure that the PCB is not under any stress such as bending or twisting. Elastomer contacts are very delicate and missing pixels could result from slight dislocation of any of the elements.
6. Avoid pressing on the metal bezel, otherwise the elastomer connector could be deformed and lose contact, resulting in missing pixels and cause rainbow on the display.
7. Be careful not to touch or swallow liquid crystal that might leak from a damaged cell. Any liquid crystal adheres to skin or clothes, wash it off immediately with soap and water.

Static Electricity Precautions:

1. CMOS-LSI is used for the module circuit; therefore, operators should be grounded whenever he/she comes into contact with the module.
2. Do not touch any of the conductive parts such as the LSI pads, the copper leads on the PCB and the interface terminals with any parts of the human body.
3. Do not touch the connection terminals of the display with bare hand; it will cause disconnection or defective insulation of terminals.
4. The modules should be kept in anti-static bags or other containers resistant to static for storage.
5. Only properly grounded soldering irons should be used.
6. If an electric screwdriver is used, it should be grounded and shielded to prevent sparks.
7. The normal static prevention measures should be observed for work clothes and working benches.
8. Since dry air is inductive to static, a relative humidity of 50-60% is recommended.

Soldering Precautions:

1. Soldering should be performed only on the I/O terminals.
2. Use soldering irons with proper grounding and no leakage.
3. Soldering temperature: $280^{\circ}\text{C}+10^{\circ}\text{C}$
4. Soldering time: 3 to 4 second.
5. Use eutectic solder with resin flux filling.
6. If flux is used, the LCD surface should be protected to avoid spattering flux.
7. Flux residue should be removed.

Operation Precautions:

1. The viewing angle can be adjusted by varying the LCD driving voltage V_o .
2. Since applied DC voltage causes electro-chemical reactions, which deteriorate the display, the applied pulse waveform should be a symmetric waveform such that no DC component remains. Be sure to use the specified operating voltage.
3. Driving voltage should be kept within specified range; excess voltage will shorten display life.
4. Response time increases with decrease in temperature.
5. Display color may be affected at temperatures above its operational range.
6. Keep the temperature within the specified range usage and storage. Excessive temperature and humidity could cause polarization degradation, polarizer peel-off or generate bubbles.
7. For long-term storage under 40C is required and the relative humidity should be kept below 60%.