



**FOCUS LCDs**  
LCDs MADE SIMPLE®

Ph. 480-503-4295 | [NOPP@FocusLCDs.com](mailto:NOPP@FocusLCDs.com)

TFT | OLED | CHARACTER | GRAPHIC | UWVD | SEGMENT | CUSTOM

## TFT Display Module

Part Number E18RE-CW1000-N

### Overview:

- 1.77-inch TFT (34.70x46.75mm)
- 8 Bit MCU Interface
- 128x160 pixels
- 6:00 Viewing Angle
- White LED backlight
- Operating Temp: -20C to 70C
- Storage Temp: -30C to 80C
- Transmissive/ Normally White
- No Touch Panel
- 1000 NITS
- Controller: ST7735S
- RoHS Compliant

## Description

This is a color active matrix TFT (Thin Film Transistor) LCD (Liquid Crystal Display) that uses amorphous silicon TFT as a switching device. This model is composed of a transmissive type TFT LCD Panel, driver circuit and a backlight unit. The resolution of the 1.77" TFT LCD contains 128(RGB)x160 pixels and can display up to 65K colors.

## TFT Features

Low Input Voltage: 3.3V

Display Colors: 65K


TFT Interface: 8 Bit MCU

General Information Items	Specification	Unit	Note
	Main Panel		
TFT Display area (AA)	28.03(H)*35.04(V) (1.77inch)	mm	-
Driver Element	TFT active matrix	-	-
Display Colors	65K	colors	-
Number of pixels	128(RGB)x160	dots	-
TFT Pixel arrangement	RGB vertical stripe	-	-
Pixel Pitch	0.219(H)*0.219(V)	mm	-
Viewing angle	6:00	-	-
Display mode	Transmissive, Normally White	-	-
TFT Controller	ST7735S	-	-
Operating temperature	-20-+70	°C	-
Storage temperature	-30-+80	°C	-


## Mechanical Information

Item		Min	Typ.	Max	Unit	Note
Module Size	Horizontal (H)		34.70		mm	-
	Vertical (V)		46.75		mm	-
	Depth (D)		2.4		mm	-
	Weight		TBD		g	

## 1. Block Diagram



# 1. Outline Dimensions



## 2. Input Terminal Pin Assignment

### 2.1 TFT

NO.	SYMBOL	DISCRIPTION	I/O
1	GND	Ground.	P
2	IOVDD	Supply voltage(1.8V).	P
3	VDD	Supply voltage(3.3V).	P
4	/CS	Chip select input pin ("Low" enable). fix this pin at VCI or GND when not in use.	I
5	/RST	This signal will reset the device and must be applied to properly initialize the chip.	P
6	D/C	-Display data/command selection pin in parallel interface. D/ C='1': display data or parameter. D/C='0': command data. -If not used, please fix this pin at VDDI or DGND.	I
7	/WR	-Write enable in MCU parallel interface. -If not used, please fix this pin at VDDI or DGND.	
8	/RD	Serves as a read signal and MCU read data at the rising edge. fix this pin at VCI or GND when not in use.	I
9-16	DB0-DB7	-8BIT Data Bus.	I/O
17	LED_A	Anode pin of backlight.	P
18-19	LED_K	Cathode pin OF backlight.	P
20	GND	Ground.	P
21-24	NC	NC	


### 3. LCD Optical Characteristics

#### 3.1 Optical Specifications

Item	Symbol	Condition	Min.	Typ.	Max.	Unit.	Note
Contrast Ratio	CR	$\Theta=0$	400	500	--		(1)(2)
Response time	Rising	$T_R$	--	2	4	msec	(1)(3)
	Falling	$T_F$	--	6	12		
Color Gamut	S(%)		40	50	--	%	
Color Filter Chromaticity	White	$W_X$	0.236	0.276	0.316		(1)(4) CA-310
		$W_Y$	0.248	0.288	0.328		
	Red	$R_X$	0.554	0.594	0.634		
		$R_Y$	0.318	0.358	0.398		
	Green	$G_X$	0.269	0.309	0.349		
		$G_Y$	0.507	0.547	0.587		
	Blue	$B_X$	0.110	0.150	0.190		
		$B_Y$	0.038	0.078	0.118		
Viewing angle	Hor.	$\Theta_L$	CR>10	35	45	--	(1)(4)
		$\Theta_R$		35	45	--	
	Ver.	$\Theta_U$		35	45	--	
		$\Theta_D$		10	20	--	
Option View Direction	6:00						

### Optical Specification Reference Notes:

(1) Definition of Viewing Angle: The viewing angle is the angle at which the contrast ratio is greater than 10. The viewing angles are determined for the horizontal or 3,9 o'clock direction and the vertical or 6,12 o'clock direction with respect to the optical axis which is normal to the LCD surface.




(2) Definition of Contrast Ratio (Cr): measured at the center point of panel. The contrast ratio (Cr) measured on a module, is the ratio between the luminance (Lw) in a full white area (R=G=B=1) and the luminance (Ld) in a dark area (R=G=B=0).

$$Cr = \frac{Lw}{Ld}$$


(3) Definition of transmittance (T%): The transmittance of the panel including the polarizers is measured with electrical driving. The equation for transmittance Tr is:

$$Tr = \frac{I_t}{I_o} \times 100\%$$



I<sub>o</sub> = the brightness of the light source.  
 I<sub>t</sub> = the brightness after panel transmission

(4) Definition of Response Time (Tr, Tf): The rise time 'Tr' is defined as the time for luminance to change from 90% to 10% as a result of a change of the electrical condition. The fall time 'Tf' is defined as the time for luminance to change from 10% to 90% as a result of a change of the electrical condition.



(5) Definition of Color Gamut:

Measuring machine CFT-01. NTSC's Primaries:  $R(x,y,Y), G(x,y,Y), B(x,y,Y)$ . FPM520 of Westar Display Technologies, INC., which utilized SR-3 for Chromaticity and BM-5A for other optical characteristics. The color chromaticity shall be calculated from the spectral data measured with all pixels first in red, green, blue and white. Measurements shall be made at the center of the panel.






Fig. 1931 CIE chromacity diagram

$$\text{Color gamut: } S = \frac{\text{Area of RGB triangle}}{\text{Area of NTSC triangle}} \times 100\%$$

(6) Definition of Optical Measurement Setup:

The LCD module should be stabilized at a given temperature for 20 minutes to avoid abrupt temperature change during measuring. In order to stabilize the luminance, the measurement should be executed after lighting backlight for 20 minutes.





## 4. TFT Electrical Characteristics

### 4.1 Absolute Maximum Rating (Ta=25 °C, VSS=0V)

Characteristics	Symbol	Min.	Max.	Unit	Note
Digital Supply Voltage	VDD	-0.3	4.0	V	Note 1
Digital interface supply Voltage	IOVDD	-0.3	4.0	V	Note 1
Operating temperature	T <sub>OP</sub>	-20	+70	°C	
Storage temperature	T <sub>ST</sub>	-30	+80	°C	

*NOTE 1: If the absolute maximum rating of the above parameters is exceeded, even momentarily, the quality of the product may be degraded. Absolute maximum ratings specify the values which the product may be physically damaged if exceeded. Be sure to use the product within the range of the absolute maximum ratings.*

### 4.2 DC Electrical Characteristics

Characteristics	Symbol	Min.	Typ.	Max.	Unit	Note
Digital Supply Voltage	VDD	2.6	3.3	4.0	V	
Digital interface supply Voltage	IOVDD	1.65	1.8	3.7	V	
Normal mode Current	IDD	--	2	6	mA	
Level input voltage	V <sub>IH</sub>	0.7*IOVDD	--	IOVDD	V	
	V <sub>IL</sub>	GND	--	0.3*IOVDD	V	
Level output voltage	V <sub>OH</sub>	0.8*IOVDD	--	IOVDD	V	
	V <sub>OL</sub>	GND	--	0.2*IOVDD	V	


### 4.3 LED Backlight Characteristics

The back-light system is edge-lighting type with 5 LED chips

Item	Symbol	Min.	Typ.	Max.	Unit	Note
Forward Current	I <sub>F</sub>	80	100	--	mA	
Forward Voltage	V <sub>F</sub>	--	3.2	--	V	
LCM Luminance	LV	1050	1100	--	cd/m <sup>2</sup>	Note3
LED life time	Hr	50000	--	--	Hour	Note1,2
Uniformity	Avg	80	--	--	%	Note3


Note 1: LED lifetime (Hr) can be defined as the time in which it continues to operate under the condition: Ta=25 ±3 °C, typical IL value indicated in the above table until the brightness becomes less than 50%.

Note 2: The “LED lifetime” is defined as the module brightness decrease to 50% original brightness at Ta=25°C and IL = 100mA. The LED lifetime could be decreased if operating IL is larger than 100mA. The constant current driving method is suggested.



B/L Circuit

Note 3: Luminance Uniformity of these 9 points is defined as below:



$$\text{Luminance} = \frac{\text{Total Luminance of 9 points}}{9}$$

$$\text{Uniformity} = \frac{\text{minimum luminance in 9 points(1-9)}}{\text{maximum luminance in 9 points(1-9)}}$$

## **5.0 TFT AC Characteristics**

### **5.1 Interface Timing**

*For the interface timing diagram, see diagram on page 49 of the data sheet for controller IC ST7735S. The data sheet can be found here <https://focuslcds.com/content/ST7735S.pdf>*

## **6.0 Quality Inspection Standards**

*For TFT quality inspection standards, please see the following link: <https://focuslcds.com/tft-quality-inspection-standards/>*

## **7.0 Cautions and Handling Precautions**

### **7.1 Handling and Operating the Module**

1. When the module is assembled, it should be attached to the system firmly. Do not warp or twist the module during assemblywork.
2. Protect the module from physical shock or any force. In addition to damage, this may cause improper operation or damage to the module and back-light unit.
3. Note that polarizer is very fragile and could be easily damaged. Do not press or scratch the surface.
4. Do not allow drops of water or chemicals to remain on the display surface. If you have the droplets for a long time, staining and discoloration may occur.
5. If the surface of the polarizer is dirty, clean it using some absorbent cotton or soft cloth.
6. The desirable cleaners are water, IPA (Isopropyl Alcohol) or Hexane. Do not use ketene type materials (ex. Acetone), Ethyl alcohol, Toluene, Ethyl acid or Methyl chloride. It might permanent damage to the polarizer due to chemical reaction.
7. If the liquid crystal material leaks from the panel, it should be kept away from the eyes or mouth. In case of contact with hands, legs, or clothes, it must be washed away thoroughly with soap.
8. Protect the module from static; it may cause damage to the CMOSICs.
9. Use fingerstalls with soft gloves in order to keep display clean during the incoming inspection and assembly process.
10. Do not disassemble the module.
11. Protection film for polarizer on the module shall be slowly peeled off just before use so that the electrostatic charge can be minimized.
12. Pins of I/F connector shall not be touched directly with bare hands.
13. Do not connect, disconnect the module in the "Power ON" condition.
14. Power supply should always be turned on/off by the item Power On Sequence & Power Off Sequence.

### **7.2 Storage and Transportation**

1. Do not leave the panel in high temperature, and high humidity for a long time. It is highly recommended to store the module with temperature from 0 to 35 °C and relative humidity of less than 70%
2. Do not store the TFT-LCD module in direct sunlight.
3. The module shall be stored in a dark place. When storing the modules for a long time, be sure to adopt effective measures for protecting the modules from strong ultraviolet radiation, sunlight, or fluorescent light.
4. It is recommended that the modules should be stored under a condition where no condensation is allowed. Formation of dewdrops may cause an abnormal operation or a failure of the module. In particular, the greatest possible care should be taken to prevent any module from being operated where condensation has occurred inside.
5. This panel has its circuitry FPC on the bottom side and should be handled carefully in order not to be stressed.