FOCUS LCDs
LCDs MADE SIMPLE®

ISO 9001
QUALITY MANAGEMENT

MEDICAL | INDUSTRIAL | DEFENSE | AGRICULTURE | FOOD SERVICE

G128128C-FTW-DW65

Product Description

- 128x128 Graphic LCD
- FSTN Positive
- 85.0x100.0mm Module
- 8-Bit Parallel Interface
- White LED Backlight

- Transflective
- Wide Temp Range
- 5.0V
- LCD IC: UCi6963
- RoHS Compliant

LCD@FocusLCDs.com | 480-503-4295

Revision History

Date	Rev. No	Page	Summary
08/09/2026	1.0	All	First issue

Graphic LCD Features

Resolution: 128x128 Dots
Interface(s): 8-Bit Parallel
RoHS Compliant.


General Information Items	Specification	Unit	Note
	Main Panel		
Viewing Area (VA)	62.0 (H) x 62.0 (V)	mm	--
LCD Type	FSTN Positive	--	--
Viewing Angle	6:00	O'Clock	--
Polarizer	Transflective	--	--
Backlight Type	LED	--	--
Backlight Color	White	--	--
LCD IC	UCi6963	--	--
Drive Mode	1/128 Duty, 1/12 Bias	--	--
Operating Temperature	-20 to +70	°C	--
Storage Temperature	-30 to +80	°C	--


Mechanical Information


Item		Min.	Typ.	Max.	Unit	Note
Module Size	Horizontal (H)	--	85.00	--	mm	--
	Vertical (V)	--	100.00	--	mm	--
	Depth (D)	--	14.00	--	mm	--
Weight		--	112	--	g	Approximate


1. Outline Dimensions

Rev.	Description	Date
1.0	First	07/01/2026









Interface:

NO	PIN
1	FG
2	VSS
3	VDD
4	VR
5	/WR
6	/RD
7	/CE
8	C/D
9	NC
10	/RES
11	DB0
12	DB1
13	DB2
14	DB3
15	DB4
16	DB5
17	DB6
18	DB7
19	FS
20	NC
21	A
22	K

NOTES:
1. DISPLAY TYPE: 128x128 FSTN GRAPHIC LCD
2. POLARIZER: TRANSFLECTIVE, POSITIVE MODE
3. VIEWING ANGLE: 6:00
4. OPERATING TEMPERATURE: -20°C TO +70°C
   STORAGE TEMPERATURE: -30°C TO +80°C
5. DRIVE METHOD: 1/128 DUTY, 1/12 BIAS,
   VDD 5.0V
6. LCD IC: UCi6963
7. BACKLIGHT: WHITE LED, 5 LEDS, 75mA, 5.0V

DISCLAIMER

DO NOT SCALE OFF THIS DRAWING. All dimensions are given in good faith and believed to be correct. These drawings are for general presentation purposes only. No responsibility can be taken with any errors found by measuring off this drawing. The Focus LCDs PDF drawing should be referenced as the master file.

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF FOCUS DISPLAY SOLUTIONS, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSIONS OF FOCUS DISPLAY SOLUTIONS, INC. IS PROHIBITED


Model Name: G128128C-FTW-DW65		FOCUS LCDs LCDs MADE SIMPLE®
General Tol: ±0.3		
Approvals	Date	Drawing No.: / Scale:
DWN:		
CHK:		Size: / Unit: mm / Page: 1/1
APP:		

2. Input Terminal Pin Assignment


NO.	Symbol	Description	I/O
1	FG	Frame ground.	P
2	VSS	Power supply (GND).	P
3	VDD	Power supply for logic (+5.0V).	P
4	VR	LCD module voltage input (-13.5V).	P
5	/WR	Write signal.	I
6	/RD	Read signal.	I
7	/CE	Chip select signal.	I
8	C/D	Command/Data select signal.	I
9	NC	No connection.	--
10	/RES	Reset signal (low effective).	I
11-18	DB0-DB7	Data bus lines.	I/O
19	FS	Font selection (H:6x8, L:8x8).	I
20	NC	No connection.	--
21	A	Power supply for LED backlight (+5.0V).	P
22	K	Power supply for LED backlight (0V).	P

3. Circuit Block Diagram

3.1 Electrical Block Diagram



3.2 Power Supply



4. LCD Optical Characteristics

Item		Symbol	Condition	Min	Typ.	Max	Unit
Contrast Ratio		CR	--	--	12	--	--
Response Time	On	T_{on}	--	--	160	240	ms
	Off	T_{off}		--	100	150	ms
Viewing Angle $C_r \geq 2$, 25°C	Hor.	Θ_L	Φ=270°, 9H	--	--	40	degree
		Θ_R	Φ=90°, 3H	--	--	40	
	Ver.	Θ_T	Φ=180°, 12H	--	--	60	
		Θ_B	Φ=0°, 6H	--	--	60	
Frame Frequency		Ff	25°C	--	70	--	Hz

5. Electrical Characteristics

5.1 Absolute Maximum Rating

Characteristics	Symbol	Min	Max	Unit
Supply Voltage	VDD-VSS	-0.3	7.0	V
	VDD-VR	0.0	26.0	V
Input Voltage	Vi	-0.3	VDD+0.3	V
Operating Temperature	T_{OP}	-20	+70	°C
Storage Temperature	T_{ST}	-30	+80	°C

NOTE: If the absolute maximum rating of the above parameters is exceeded, even momentarily, the quality of the product may be degraded. Absolute maximum ratings specify the values which the product may be physically damaged if exceeded. Be sure to use the product within the range of the absolute maximum ratings.

5.2 DC Electrical Characteristics

Characteristics		Symbol	Condition	Min	Typ.	Max	Unit
LCD Driving Voltage		VDD-VR	--	--	18.5	--	V
Supply Voltage For Logic		VDD-VSS	VDD=5V	4.5	5.0	5.5	V
Input Voltage	H Level	V_{IH}	--	2.2	--	VDD	V
	L Level	V_{IL}	--	0.0	--	0.6	V
Supply Current For Logic		I_{CC}		--	15.5	37.0	mA
Supply Current For LCD		I_O		0.15	0.22	0.27	mA


Condition:

1. VDD = 5.0V
2. 1/128 Duty, 1/12 Bias
3. Ta=25°C

6. Module Function

6.1 Timing Characteristics

System Bus Timing for 8080 MCU Interface




(VDD=5V±5%, GND=0V, Ta=-20~70°C)

Item	Signal	Symbol	Condition	Rating		Units
				Min.	Max.	
C/D Set-up Time	C/D	t_{CDS}		13	--	ns
C/D Hold Time		t_{CDH}		13	--	
/CE, /RD, /WR Pulse Width	/CE, /RD, /WR	t_{CE}, t_{RD}, t_{WR}		100	--	
Data Set-up Time	DB0~DB7 (Write)	t_{DS}		100	--	
Data Hold Time		t_{DH}		50	--	
Access Time	DB0~DB7 (Read)	t_{ACC}		--	190	
Output Hold Time		t_{OH}		--	65	

Note:
*1. Input signal rise time and fall time (tr, tf) is specified at 20ns or less.
*2. Please see the UCi6963 sheet for details.

6.2 Reset Timing



(VDD=5V±10%, VSS=0V, Ta=25°C)

Item	Signal	Symbol	Condition	Rating			Units
				Min.	Typ.	Max.	
Reset time		t_R		--	--	100	μs
Reset “L” pulse width	RST	t_{RW}		100	--	--	μs

6.3 LCM Application

For application examples, please see information on pages 36-38 of the data sheet for LCD controller UCi6963. The data sheet can be found here:
https://focuslcds.com/wp-content/uploads/Drivers/UCi6963.pdf

6.4 Command Table

COMMAND	CODE								PARA	FUNCTION	EXECUTION TIME
	D7	D6	D5	D4	D3	D2	D1	D0			
REGISTERS SETTING	0	0	1	0	0	N2	N1	N0	2	N2 N1 N0 0 0 1 SET CURSOR POINTER 0 1 0 SET OFFSET REGISTER 1 0 0 SET ADDRESS POINTER	STATUS CHECK
SET CONTROL WORD	0	1	0	0	0	0	N1	N0	2	N1 N0 0 0 SET TEXT HOME ADDRESS 0 1 SET TEXT AREA 1 0 SET GRAPHIC ADDRESS 1 1 SET GRAPHIC AREA	STATUS CHECK
MODE SET	1	0	0	0	CG	N2	N1	N0	-	CG=0: CGROM MODE CG=1: CGRAM MODE N2 N1 N0 GRAPHIC AND TEXT 0 0 0 "OR" 0 0 1 "EXOR" 0 1 1 "AND" 1 0 0 TEXT ATTRIBUTE MODE	
DISPLAY MODE	1	0	0	1	N3	N2	N1	N0	-	N3=0: GRAPHIC OFF N3=1: GRAPHIC ON N2=0: TEXT OFF N2=1: TEXT ON N1=0: CURSOR OFF N1=1: CURSOR ON N0=0: BLINK OFF N0=1: BLINK ON	32x1/f_{osc}
CURSOR PATTERN SELECT	1	0	1	0	0	N2	N1	N0	-	N2, N1, N0 SET THE LINES OF CURSOR N2 N1 N0 0 0 0 1-LINE CURSOR . . . 1 1 1 8-LINE CURSOR	
DATA AUTO READ/WRITE	1	0	1	1	0	0	N1	N0	-	N1 N0 0 0 SET DATA AUTO WRITE 0 1 SET DATA AUTO READ 1 * AUTO RESET	
DATA READ/WRITE	1	1	0	0	0	N2	N1	N0	1	DATA WRITE AND READ BY 1 N2=0: INCREMENT / DECREMENT ADP N2=1: NONVARIABLE ADP N1=0: INCREMENT ADP 1 N1=1: DECREMENT ADP 1 N0=0: DATA WRITE N0=1: DATA READ	

COMMAND	CODE								PARA	FUNCTION	EXECUTION TIME
	D7	D6	D5	D4	D3	D2	D1	D0			
SCREEN PEEK	1	1	1	0	0	0	0	0	-	SCREEN PEEK	
SCREEN COPY	1	1	1	0	1	0	0	0	-	SCREEN COPY	
BIT SET/RESET	1	1	1	1	N3	N2	N1	N0	-	BIT RESET N3=0: BIT 0 N3=1: BIT 1	

7. Cautions and Handling Precautions

7.1 Handling and Operating the Module

1. When the module is assembled, it should be attached to the system firmly. Do not warp or twist the module during assembly work.
2. Protect the module from physical shock or any force. In addition to damage, this may cause improper operation or damage to the module and back-light unit.
3. Note that polarizer is very fragile and could be easily damaged. Do not press or scratch the surface.
4. Do not allow drops of water or chemicals to remain on the display surface. If you have the droplets for a long time, staining and discoloration may occur.
5. If the surface of the polarizer is dirty, clean it using some absorbent cotton or soft cloth.
6. The desirable cleaners are water, IPA (Isopropyl Alcohol) or Hexane. Do not use ketene type materials (ex. Acetone), Ethyl alcohol, Toluene, Ethyl acid or Methyl chloride. It might permanent damage to the polarizer due to chemical reaction.
7. If the liquid crystal material leaks from the panel, it should be kept away from the eyes or mouth. In case of contact with hands, legs, or clothes, it must be washed away thoroughly with soap.
8. Protect the module from static; it may cause damage to the CMOS ICs.
9. Use fingerstalls with soft gloves in order to keep display clean during the incoming inspection and assembly process.
10. Do not disassemble the module.
11. Protection film for polarizer on the module shall be slowly peeled off just before use so that the electrostatic charge can be minimized.
12. Pins of I/F connector shall not be touched directly with bare hands.
13. Do not connect, disconnect the module in the “Power ON” condition.
14. Power supply should always be turned on/off by the item Power On Sequence & Power Off Sequence.

7.2 Storage and Transportation

1. Do not leave the panel in high temperature, and high humidity for a long time. It is highly recommended to store the module with temperature from 0 to 35 ℃ and relative humidity of less than 70%.
2. Do not store the LCD module in direct sunlight.
3. The module shall be stored in a dark place. When storing the modules for a long time, be sure to adopt effective measures for protecting the modules from strong ultraviolet radiation, sunlight, or fluorescent light.
4. It is recommended that the modules should be stored under a condition where no condensation is allowed. Formation of dewdrops may cause an abnormal operation or a failure of the module. In particular, the greatest possible care should be taken to prevent any module from being operated where condensation has occurred inside.
5. This panel has its circuitry FPC on the bottom side and should be handled carefully in order not to be stressed.